Angle Grinder Pads



MAXIMUM OPERATIONAL SPEED TABLE

Pad size in mm	Maximum operating speed	Max RPM
100mm	80 m/s	15,300
115mm	80 m/s	13,300
125mm	80 m/s	12,250
150mm	80 m/s	10,200
180mm	80 m/s	8,500
230mm	80 m/s	6,650

CONVERSION TABLE

100mm	4"	180mm	7"
115mm	4 1/2"	200mm	8"
125mm	5″	225mm	9"
150mm	6"		

THE RIGHT BACK UP PAD

ABRASIVE DISC

OPTION 1



OVERLAPPING


- ✓ OPTIMUM USE OF THE ABRASIVE DISC
- ✓ MORE ACCURATE WORK IN TIGHT CORNERS
- ✓ ABRASIVE DISCS LAST LONGER





ABRASIVE DISC

OPTION 2



NON OVERLAPPING

- ✓ BETTER FOR HEAVY DUTY
- ✓ IDEAL ON IRREGULAR SURFACES

(bolt heads ...)





This range can be considered for universal use

Abrasive in mm	Pad in mm	Pad height in mm	Thread	Grits	Spanner	Reference
100	90	15	M10 x 1.50	60 + Finer	Green 24015	20022
115	104	15	M14 x 2	60 + Finer	Zinc 24065	20117
125	116	20	M14 x 2	60 + Finer	Zinc 24065	20212
125	123	20	5/8 UNC	60 + Finer	Zinc 24065	
180	171	20	M14 x 2	60 + Finer	Zinc 24065	20312
180	171	27	5/8 UNC	60 + Finer	Blue 24040	20405

Medium Flexibility - BLACK

Medium Flexibility - WHITE - Our best selling pad range


This range can be considered for universal use

Triis rarige		orisiacica for ai					
Abrasive in mm	Pad in mm	Pad height in mm	Threa	ad	Grits	Spanner	Reference
100	90	15		3/8 x 24	60 + Finer	Green 24015	20030
115	104	14.5		M14 x 2	60 + Finer	Zinc 24065	20115
180	171	20		M14 x 2	60 + Finer	Zinc 24065	20310
230	220	20		5/8 UNC	60 + Finer	Zinc 24065	20505
230	220	20		M14 x 2	60 + Finer	Zinc 24065	20510





Spanners



Spanners

Ultra tough design. Colour coded for easy identication

Colour	Dimensions in mm	To Fit	Reference
GREEN	20 - 4	Flexipads 100mm grinders and most electric machines	24015
BROWN	23 - 5	Flexipads M10, Black & Decker 100 and 115mm	24020
YELLOW	28 - 4	Makita 125mm Grinders	24030
WHITE	30 - 4	Bosch 115mm, Desoutter 308-354	24035
BLACK	32 - 5	Black & Decker HD Series, Perles 180 and 230mm	24045
RED	35 - 5	All Flexipads Ma4, Flexipads Easy-Lok, AEG, Black & Decker, Bosch, C.P Industrial, Flex, Hitachi, Kress, Makita, Matebo, Ryobi, Super Stork, Teksan 180 and 230mm	24060
ZINC	Open Ended 14 & 17	Most brands	24070



Dual Action Orbital Sander Pads



Thick Profile - Unique straight edge lip

Our best selling pad range

Abrasive in mm	Surface	Holes	Thread	Foam Layer in mm	Density	Max RPM	Reference
125	Velcro	No Hole	5/16 UNF	16	Medium	10,000	32305
150	Velcro	No Hole	5/16 UNF	16	Medium	10,000	32315
150	Velcro	6 Holes E80	5/16 UNF	16	Medium	10,000	32320





ULTIMATE



Soft Interface Cushion Velcro - (Other configurations available MOQ 250 pcs)

Placed between pad and abrasive disc to create a very soft sanding surface


Abrasive in mm	Pad in mm	Specification	Foam Layer in mm	Density	Max RPM	Reference
150	148	No Hole	12	Soft	13,000	32705
150	148	6 + 1 Holes	12	Soft	13,000	32710






Sander Polisher Pads














MUSHROOM HOOK

MICRO HOOK

т ноок

ICONS FOR FLEXIBILITY

	SOFT	80 + FINER
	MEDIUM	60 + FINER
0	FIRM	60 + FINER
0	HARD	36 + FINER
0	RIGID	16 + FINER

MAXIMUM OPERATIONAL SPEED TABLE

Pad size in mm	Maximum operating speed	Max RPM
100mm	80 m/s	15,300
115mm	80 m/s	13,300
125mm	80 m/s	12,250
150mm	80 m/s	10,200
180mm	80 m/s	8,500
230mm	80 m/s	6,650







12mm



Medium Density Velcro - (For a M14 to M10 x 1.50 adapter please quote Ref. 13450)

Fantastic resistance to damage and lasts longer than most identical pads available today

	6115
115 113 M14 x 2 12 Medium 13,300 36	5115
	6125
125 123 M14 x 2 12 Medium 12,250 36	6140
125 123 5/8 UNC 12 Medium 12,250 36	6145
150 148 M14 x 2 12 Medium 10,200 36	6155
150 148 5/8 UNC 12 Medium 10,200 36	6160







12mm


Soft Density Velcro - Water feed holes can be added if not shown

Versatile pads efficient on curved surfaces. The outer edge is angled for precise work

Abrasive in mm	Surface in mm	Thread	Foam Layer in mm	Density	Max RPM	Reference
125	123	M14 x 2	12	Soft	12,250	36305
150	148	5/8 UNC	12	Soft	10,200	36320









Buffing & Polishing Foams

ICONS FOR FLEXIBILITY

	ULTRA SOFT	GLAZING
(SOFT	POLISHING
0	MEDIUM	COMPOUNDING/POLISH
0	FIRM	COMPOUNDING
0	HARD	CUTTING

FOAM USES

Glaze	Polish	Compound	Cut
YELLOW			
WHITE			
ORANGE			

PINK

PINK

BLACK



ULTIMATE

ULTIMATE





WHITE Compounding

This very firm material is ideal when compounding all modern paints including LVHM

Dimension mm	Specification	Matching Velcro Pad	Max RPM	Reference
150 x 50	M14 x 2		2,500	44005
150 x 50	5/8 UNC		2,500	44010
150 x 50	Velcro	36350 (M14), AP096 (5/16)	2,500	44015
80 x 25	Velcro	Ap003 (M14), 17000, (5/16")	2,500	44416



YELLOW Heavy Compounding

Yellow is a coarse, open-celled foam designed for heavy cutting of oxidised paints

	, , ,		<u> </u>	
Dimension in mm	Specification	Matching Velcro	Pad Max RPM	Reference
150 x 50	M14 x 2		2,500	44305



BLUE Regular Compounding and Polishing

An all purpose foam with a medium grade density

Dimension in mm	Specification	Matching Velcro Pad	Max RPM	Reference
150 x 50	M14 x 2		2,500	44105
150 x 50	Velcro	36350 (M14), AP096 (5/16)	2,500	44115



PINK Regular Polishing

Soft polishing foam which works very well on dark colours

Dimension in mm	Specification	Matching Velcro Pad	Max RPM	Reference
150 x 50	M14 x 2		2,500	44205



RED Polishing

Designed to allow the free flow of air. Perfect for final polishing ultra soft.

Dimension in mm	Specification	Matching Velcro Pad	Max RPM	Reference
150 x 50	M14 x 2		2,500	44425
80 x 25	Velcro	AP003 (M14), 17000 (5/16)	2,500	44417
150 x 50	Velcro	36359 (M14), AP096 (5/16)	2,500	44420







Polishing Bonnets



Regular Velcro

100% pure new wool, 20mm wool height

Size in mm	Thickness	Matching Support Pad	Max RPM	Reference
125	20mm	AP001 (M14)	2,500	40220



Tie Cord Bonnet Support Pads

Soft support pads designed for wool. If size not found use above pads

Bonnet in mm	Support pad in mm	Thread	Specification	Max RPM	Reference
180	160	M14 x 2	Tie Cord	2,500	40325



Detailing

Drying BLUE Wonder Towels

Thanks to its waffle pattern, this king size towel (75 x 60cm) absorbs vast amounts of water very quickly. Its soft fabric has been chosen to make sure the drying operation will not leave any swirl marks or dust. The satin edge is an extra protection against unexpected damages. 2 per pack.

Description	Reference
75 x 60cm 'Scratchless' BLUE WONDER Drying Towels x 2	40525



Buffing WHITE Wonder Towels

Buff, wax and wipe without swirls! They are super plush and have the no-scratch edging professionals demand. They can be used on almost any surface. Designed around the newest generation of microbre fabric they have the ideal weight to avoid being too heavy once wet. They excel at buffing off carnauba waxes and sealants. 2 per pack.

Description	Reference
40 x 40cm 'Scratchless' WHITE Wonder Buffing Towels x 2	40532



Polishing GREEN Wonder Towels

These edgeless towels will not scratch the paint as they are made from nothing but the finest 75/25 blend of microfibre, but more importantly have no binding. Using the latest in microfibre technology and high frequency cutting they are made without the need for an edge. 2 per pack.

Description	Reference
40 x 40cm 'Scratchless' GREEN WONDER Polishing Towels x 2	40535



Wheel Cleaning Brushes (Not available in the USA)

These unique brushes are made from a soft yet porous synthetic material that will grab grime and lift it off the wheel. Its wedge shape allows you to get into small areas. The handle is comfortable and moulded to fit your hand. Great for motorcycles too! 3 per pack.

Description	Reference
Wheel Scrubber x 3	40650
Wheel Cleaning Brush Long Handle 3 per Pack	40655



Spindle Pads & Abrasives

PSA & Velcro Spindles

A classic spindle pad for multiple uses

Size in mm	Spindle Fitting		Max RPM	Reference
50	6mm Velcro	Abrasive Discs available below	30,600	48110
75	6mm Velcro	Abrasive Discs available below	20,125	48115



Velcro SOFT Spindles

The conical shape of 48220 and 48215 allows for more accurate work in difficult situations.

Size in mm	Spindle Fitting	Foam Layer in mm	Density	Max RPM	Reference
25	3mm	20	Soft	40,100	48205
50	6mm	20	Soft	30,600	48210
75	6mm	20	Soft	20,125	48215



Abrasive Velcro Discs

(x 100) order as $100 \times 48405 = 1$ box

Abrasive in mm	Grits	Reference
25	P60	48405
25	P120	48410
25	P180	48415
25	P240	48420
25	P400	48425
50	P60	48505
50	P120	48510
50	P180	48515
50	P240	48520
75	P60	48605
75	P120	48610
75	P180	48615
75	P240	48620



Adapters

To suit all Flexipads with a M14 Thread

Specification		Reference
M14 to 8mm Spindle	Zinc	13400



Drill Accessories

Flexible Shaft Drill Sander Velcro

Developed for both soft and hard sanding. It uses a spring and bayonet system to meet a wide range of applications. Available in 125mm with a 6mm spindle shaft. Abrasives available.

Size in mm	Specification	Max RPM	Reference
125	6mm Shaft	12,250	11960



Drill & Sander Polisher Velcro

Product	Specifications	Application	Reference
Kit spares	Backing Pad for Drill	Velcro	88010
Kit spares	Polishing foam	Velcro	88015
Kit spares	All Wool Bonnet		88020





